



FABRICATING MACHINERY
WELDING SOLUTIONS

BENDMAK
BENDING & DRILLING & WELDING SOLUTIONS

www.bendmak.com.tr

BPP 80



OPTIONAL FEATURES

- Marking (when this feature is requested, the number of punching head is two)
- Maximum 8 characters can be marked as group. Character size is 5/8"x5/16". For marking with more characters, it is required to move the plate and place suitable characters.

PLATE PUNCHING MACHINES



BPP 80 TECHNICAL INFORMATION

Model	Maximum Punch Capacity (ton-force Short)		Material Thickness with Standard Tools		Max. Punching Diameter (inch)	Punching max. thickness with shear strength 58,000 PST dia. Max. Through (inch)	Maximum plate size with programmed repositioning (inch)	X and Y axes positioning stroke (inch)	Positioning speed through X Axes (ft/min)	Positioning speed through Y Axes (ft/min)	Maximum plate weight at a standard positioning speed (lbs)	Punches	(Optional) Marking Features	1 Marking and 2 Punches featured set	Characters per marking group	Size of characters (inch)	Table Dimensions (inch)
	min	max	min	max													
BPP 80	88	11 ga.	1"		Ø1-13/16	Ø1-1/4x13/16	20	40x20	65	65	220	3		1	8	5/8x5/16	Customer Specific

Bendmak reserves the right to change all above specifications without prior notice.

