

# TANK ROTATING

Bendmak CR rotators are designed to improve speed for manual and automatic welding. These rolls will minimize overhead crane usage allowing increased production in other area in the shop. Bendmak's standard capacities range from 3 - 300 Tons but this can be increased if requested.



## CR Conventional Rotators

- Up to 300 Ton Standard Capacity
- Non slip polyurethane wheels
- Digital speed indicator
- Manual diameter adjustments



10417 S. County Rd 39, Lithia FL 33547  
Phone: (833) BENDMAK | (833) 236-3625  
[www.bendmakusa.com](http://www.bendmakusa.com) | [sales@bendmakusa.com](mailto:sales@bendmakusa.com)

(833) BENDMAK  
[www.bendmakusa.com](http://www.bendmakusa.com)

# STANDARD & OPTIONAL EQUIPMENT

## Standard



- Adjustable rotation speed
- "PU" rollers absorbing shocks & vibrations
- Manual diameter adjustment
- motors w/ brake
- 15' cable length to control
- Digital speed indicator

## Options

- Custom wheel designs for areas that require high temperature
- Automatic diameter / wheel axis adjustment
- Axial movement on wheels
- Synchronous operation w/ column & boom systems
- Grounding brush



## INCREASE SPEED & EFFICIENCY

Bendmak's tank rotators allow you to easily rotate a cylindrical part up to 300 Tons to acquire the most optimal positions for both manual and automated welding.

# BCR CAPACITY

BCR - 1	2.200
BCR - 3	6.600
BCR - 5	11.000
BCR - 10	22.000
BCR - 20	44.000
BCR - 30	66.000
BCR - 40	88.000
BCR - 50	110.000
BCR - 60	132.000
BCR - 80	176.000
BCR - 100 *	220.000
BCR-150 *	330.000
BCR-200 *	440.000
BCR-300 S *	660.000
BCR-300 P *	660.000

